


PFT RONDO superlight

So light you almost forget it's there.







It often only becomes apparent just how heavy some things are, when they suddenly become lighter. With its ultralight weight, you will barely notice the new PFT RONDO superlight material hose - during transport and when plastering. It will lighten your workload! It is also easy to change the two-part hydraulically integrated mortar coupling: with a simple thread. In future, take your work more lightly!

- Ultralight
- 3-fold burst pressure
- Hydraulic integration
- Mortar coupling simple to exchange
- PUR core - high abrasion resistance



ADVANTAGES AT A GLANCE

		<p>Material hose RONDO superlight:</p> <ul style="list-style-type: none"> Comfortable and simple to use PUR core (1 mm) – high abrasion resistance according to DIN 14811 <p>1 Hose kink protection at male part</p> <p>Mortar coupling:</p> <ul style="list-style-type: none"> 2 Regular TÜV testing 3 Easy to change the two-part hydraulically integrated mortar coupling with a thread 4 High mortar throughput 5 High tolerances with fit – safety 6 Precise positioning of the pin inside the hole 7 Smooth sealing surface <p>High material quality – malleable cast iron:</p> <ul style="list-style-type: none"> Reduced crack formation Increased pressure stability, resilience and breakage resistance Fully galvanised or produced from aluminium – avoidance of corrosion High component strength <p>Products</p> <ul style="list-style-type: none"> RONDO superlight flex DN25 – 5 m Part no. 00 66 73 49 RONDO superlight flex DN25 – 10 m Part no. 00 66 73 48
		
		


FIELDS OF APPLICATION

- Gypsum plaster
- Lime cement plaster (grain size ≤ 3 mm)



TECHNICAL DATA

Connection type	Mortar coupling
Hose specification	
Weight 5 m 10 m	2.9 kg 4.3 kg
Inner diameter	25 mm
Operating pressure	max. 40 bar
Burst pressure	125 bar
Bend radius	200 mm

<p>The PFT service guarantee</p> <p>Customer proximity, technical competence and service orientation. That is what PFT will continue to stand for with its sales and service centres in the coming decades.</p> <p> Click. Discover. Experience.</p> <p>www.pft.net/rondo www.youtube.com/knaufpft</p> <p>Download now! APP: PFT – Plastering Technology</p>	<p>Knauf PFT GmbH & Co. KG Einersheimer Str. 53 97346 Iphofen</p> <p>Technical Hotline +49 9323 31-1818</p> <p>Phone +49 9323 31-760</p> <p>Fax +49 9323 31-770</p> <p>info@pft.net www.pft.net</p>	<p>All rights and technical changes are reserved. Our guarantee only relates to the perfect quality of our machines. Consumption, quantity, execution details and performance data are empirical values, which cannot be transferred readily in case of different circumstances. Furthermore, the guidelines of the material manufacturer are always applicable. Changes, reprints and photo-mechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.</p> <p>PFT RONDO superlight – EN/03.20/PFT</p>
---	---	---